

## SL-1210MK2EB DJ Turntable

World Renowned Quartz Direct Drive Platter

Precision Moulded Aluminium Diecast Cabinet

1.5kg(cm) Torque for Fast Start-ups

0.8% Pitch Shift with Centre Indent

0-3g Anti Skate

Black Finish



The Legendary DJ Turntable.

### Turntable section

|                                 |   |
|---------------------------------|---|
| <b>Type</b>                     | Quartz direct drive, Manual turntable                                     |
| <b>Drive method</b>             | Direct drive  |
| <b>Motor</b>                    | Brushless DC motor  |
| <b>Turntable platter</b>        | Aluminum diecast, Diameter 33.2 cm (13-5/64"), Weight 2 kg (4.4 lb.)      |
| <b>Turntable speeds</b>         | 33 1/3 and 45 rpm   |
| <b>Variable range pitch</b>     | 0-8% with Centre Indent   |
| <b>Starting torque</b>          | 1.5 kg / cm   |
| <b>Build-up characteristics</b> | 0.7 sec. from standstill to 33 1/3 rpm                                    |
| <b>Braking system</b>           | Electronic brake  |
| <b>Wow and flutter</b>          | 0.01 % WRMS<br>0.025% WRMS (JIS C5521)<br>±0.035% peak (IEC 98A Weighted) |
| <b>Rumble</b>                   | -56 dB (IEC 98A Unweighted)<br>-78 dB (IEC 98A Weighted)                  |

### Tonearm section

|                                    |                          |
|------------------------------------|--------------------------|
| <b>Type</b>                        | Universal                |
| <b>Effective length</b>            | 230 mm (9-1/16")         |
| <b>Arm height adjustment range</b> | 0-6 mm                   |
| <b>Overhang</b>                    | 15 mm (19/32")           |
| <b>Effective mass</b>              | 12 g (without cartridge) |

|  |  |
|--|--|
| <b>Offset angle</b>                      | 22°  |
| <b>Friction</b>                          | Less than 7 mg (lateral, vertical)   |
| <b>Tracking error angle</b>              | Within 2° 32' (at the outer groove of 30 cm (12") record)<br>Within 0° 32' (at the inner groove of 30 cm (12") record) |
| <b>Stylus pressure adjustment range</b>  | 0 - 2.5 g  |
| <b>Applicable cartridge weight range</b> | 6 - 10 g<br>13.5 - 17.5 g (including headshell)  |
| <b>Headshell weight [g]</b>              | 7.5  |

## General

|                     |                                   |
|---------------------|-----------------------------------|
| <b>Power Supply</b> | ~110-120 / 220-240 V, 50 or 60 Hz |
|---------------------|-----------------------------------|

## Dimensions [mm]

|                              |       |
|------------------------------|-------|
| <b>Width</b>                 | 453.0 |
| <b>Height</b>                | 162.0 |
| <b>Depth</b>                 | 360.0 |
| <b>Weight [kg]</b>           | 12.5  |
| <b>Power Consumption [w]</b> | 13.5  |